

Osnovni podatci

Max. udaljenos od utičnice	65 m
Max. broj istovremenih korisnika	1
Prosečna površina delovanja	800 m ²
Posečan broj utičnica	15

Vacuum unit specifications

Primary filter	Cyclonic filtration
Secondary filter	Textile filter
Capacity	18 L
Unit dimensions (W x H x D)	0,38 x 1,00 x 0,40 & 0,38 x 0,35 x 0,40
Required mounting space	0,80 x 1,75 x 0,75



Motor specifications

General	220 - 250 VAC, 50 Hz	Insulation class E
Nom. power	2 x 1200 W	
Max. power	2 x 1450 W	
Max. current	2 x 6,0 A	
Max. revolutions	24628 / min	
Fuse rating	2 x 8 A	
Motorframe	145 mm	
Carbon brushes	Ref. 33415-3	
Motor control	12 VDC signal with safety transformer (VDEO551 - relay 16A)	

Turbine specifications

Motor Type	By-Pass	Exterior 50mm outlet
Number of stages	2 x 2	
Max. Negative Pressure	4200 mm H ₂ O	
Max. Airflow	49,5 L/sec	
Max. AirWatts	801 W	

Availability

1.0040.3001	Central vacuum unit MI 3001S - PC/ABS - Normal textile filter
1.0044.3001	Central vacuum unit MI 3001S - PC/ABS - Normal textile filter - Isolated
1.0050.3001	Central vacuum unit MI 3001S - PC/ABS - Self-cleaning textile filter
1.0055.3001	Central vacuum unit MI 3001S - PC/ABS - Self-cleaning textile filter - Isolated

Certification

CE	Comform
----	---------



IMPORTANT NOTE

Technical data is subject to change without notice. Please check our website for latest information.